

Technical Data Sheet

FOR

Fixed Rack Mounted Type

ODF

OPZJJ-CL-12DLC-1U

Description

OPZ/JJ Series fiber terminal box can be applied in the branch connection of fiber termination, working as distribution box, Standard 19" 1U rack mounted size, 12 ports Duplex, available for the installation of FC, SC, ST, LC adaptors.

Features

- All property indexes are in accordance with National YD/T925—1997 Standard.
- The body make use of cold rolling steel sheet Strong adhesive force, artistic and durable.
- Cable entrance are sealed with oil resistance NBR to increase the flexibility. Users can choose to prick the entrance and exit.
- Overlapping fiber-melting tray and separate insulation earth unit make the disposition of the cores, expanding the capacity and cable-earthen flexible, convenient and safe.

Structure

Configuration:

1. equipped with 24 fibers splice capacity, 24 SM LC/UPC pigtails, splice trays, 12xLC/UPC duplex adapters and connectors
2. Available for the transforming of FC, SC, ST, LC adaptors.



Technical specifications

- optical fiber winding radius: $\geq 40\text{mm}$
- extra loss of fiber tray: none
- fiber length left in tray: $\geq 1.6\text{m}$
- working temperature: $-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$
- lateral pressure-resistance: 500N
- shock-resistance: 750N

Shenzhen Optichina Technology Ltd.